

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
30 June 2005 (30.06.2005)

PCT

(10) International Publication Number
WO 2005/059372 A1

(51) International Patent Classification⁷: **F15B 11/024**,
21/14

(21) International Application Number:
PCT/EP2004/053526

(22) International Filing Date:
16 December 2004 (16.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0329243.0 17 December 2003 (17.12.2003) GB

(71) Applicant (for all designated States except US): **THALES UK PLC** [GB/GB]; 2 Dashwood Lang Road, The Bourne Business Park, Addlestone near Weybridge, Surrey KT152NX (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **GROSSART, Stuart, James, Cameron** [GB/FR]; Thales Intellectual Property, 31-33, Avenue Aristide Briand, F-94117 Arcueil (FR).

(74) Agents: **LUCAS, Laurent** et al.; Thales Intellectual Property, 31-33, Avenue Aristide Briand, F-94117 Arcueil (FR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: APPARATUS AND METHODS FOR ACTUATION



(57) Abstract: There is disclosed an actuator (5) having an actuator chamber (6) and actuator piston (9) therein defining an extend chamber (10) and a retract chamber (7) separated from the extend chamber by the actuator piston. A first fluid pump (A) is in fluid communication with the extend chamber and the retract chamber and is arranged to transfer therebetween volumes of fluid substantially equal in magnitude to changes in the volume of the retract chamber resulting from movement of the actuator piston within the actuator chamber. A second pump B connected to the extend chamber and to an accumulator (17) allows the differential volume between the extend and retract chambers to be displaced into the accumulator at a pressure. Stored accumulator fluid pressure enables pump B to be back-driven so that it behaves as a motor whenever the pressure in conduit 15 is less than in conduit 16. A pre-charge (20) unit pressurises the system until full mass counterbalance of the suspended load is achieved. In this state little or no input power from the servo motor (via pumps A & B) will be needed and significant energy savings can be made.

WO 2005/059372 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.